

4TB

Reduced wiring valve

4, 5 port pilot operated valve

Overview

4TB series is PLC compatible reduced wiring 4, 5 port valve whose plug-in coils are integrated to one side. Applicable cylinder bore size is $\varnothing 20$ to $\varnothing 180$, and wide variations.

Features

Wide option variation

Various spacers, protection structure IP65 (4TB3/4) etc. are available.

Light weight, small size

Heat proof resin, push in joint, DIN rail method (4TB1/2) etc. are available.

Flexible expansion/reduction of station No.

Block manifold method is used.

PLC control

Wide wiring variations such as serial transmission and common gland etc. are available. These are compatible with UNIWIRE SYSTEM and other network systems.

Easy plumbing and maintenance

Plug-in block manifold remarkably reduced dead space. Flat and simple design.



CONTENTS

Series variation	622
Variation of electric connection (electric connection method / circuit diagram)	624
▲ Safety precautions	625
Discrete	
● 5 port valve (4TB3/4)	626
Reduced wiring block manifold	
● 4 port valve (MN4TB1/2)	632
Reduced wiring manifold	
● 5 port valve (M4TB3/4)	642
Block configurations	
4 port valve (MN4TB1/2)	654
5 port valve (M4TB3)	660
5 port valve (M4TB4)	663
Technical data	
(1) Notes when wiring	666
(2) Pneumatics system selection guide	674
(3) How to disassemble/assemble block manifold	676
(4) Manifold part	677
Block manifold specifications and wiring specifications	
4 port valve (4TB1/2)	678
5 port valve (4TB3/4)	683

MN3E0
MN4E0

4GA/B

M4GA/B

MN4GA/B

4GA/B
(Master)

W4GA/B2

W4GB4

MN3S0
MN4S0

4TB

4L2-4/
LMF0

4SA/B0

4SA/B1

4KA/B

4F

PV5G/
CMF

PV5/
CMF

3MA/B0

3PA/B

P/M/B

NP/NAP/
NVP

4F*0E

HMV
HSV

2QV
3QV

SKH

PCD/
FS/FD

Ending

4, 5 port pilot operated valve