NP/NAP/NVP

Large flow rate 3 port valve

For air, low vacuum

Overview

This is the large flow rate 3 port valve incorporating a high seal poppet structure.

The following two series are available to match all applications. Internal pilot type NP Series suitable for driving cylinders up to ø400. External pilot type NAP/NVP Series for use with both positive and negative pressures (vacuum).

Features

Two series for all applications

- Internal pilot type NP Series NC (normally closed) type, NO (normally open) type
- External pilot type NAP/NVP Series Universal type

Compact, light weight design Large flow rate (effective sectional area up to 630 mm²) Pre-lubrication Free mounting attitude Both positive and negative pressures possible with the external pilot type Poppet structure



CONTENT	S	
▲ Safety precautions		498
3 port solenoid valve for air	NP13/NP14	500
3 port valve for air/low vacuum	NAP11	506
 3 port solenoid valve for air/low vacuum 	NVP11	510
CAD Electronic Catalog file list		515

Always read the precautions in the Introduction and page 498 before starting use.

HNB/G

HSR/G

FAB/G FGB/G

FWB/G

FHB

FLB AB

AG

AD

APK/ ADK For dry air

Explosion proof HVB/ HVL

SAB/ SVB NP/NAP/

CHB/G

MXB/G

Other G.P.

systems PD/FAD/ P.J CVE/

CVSE CPE/ CPD

Medical analysis Custom

order -arge flow rate 3 port valve