CVE2/CVSE2 CVE3/CVSE3

(Coolant valve)

I For coolant

Air operated 2, 3 port valve (coolant control)

Series variation

Overview

This is a reliable 2, 3 port coolant valve with cylinder drive method.

This valve for tool machine cutting oil or coolant control incorporates a metal seal to prevent the entry of cutting chips, abrasive grains and foreign debris, and ensures highly reliable control.

The air operated type and solenoid valve mounted type are available. These can be used in precise machines.

Features

High corrosion resistant materials

Cast iron body, and stainless steel metal seal used in valve seat. NBR or FKM packing seal can be selected. Materials optimum for coolant are used.

Certain operation

Certain operation is enabled with external pilot air operated cylinder.

Water hammer prevented (Only 2 port valve)

Resistant to foreign matter A metal seal is used.

Usable in flammable

environment.

(Air operated type)

CONT

▲Safety precautions		702
 Product introduction 		706
Low pressure (0.5 MPa and 1.	0 MPa), 2 port valve	
 Air operated type 	CVE2, CVE22-05/10	708
 Solenoid valve mounted type 	CVSE2, CVSE22-05/10	708
Medium pressure (1.6 MPa an	nd 3.0 MPa), 2 port valve	
 Air operated type 	CVE2, CVE22-16/30	718
 Solenoid valve mounted type 	CVSE2, CVSE22-16/30	718
High pressure (7.0 MPa), 2 port valve		
 Air operated type 	CVE2, CVE22-70	726
 Solenoid valve mounted type 	CVSE2, CVSE22-70	726
Medium/high pressure (3.5 MPa and 7.0 MPa), 3 port valve		
 Air operated type 	CVE3-35/70	732
 Solenoid valve mounted type 	CVSE3-35/70	732
Low pressure (0.3 MPa), 3 por	rt valve	
 Air operated type 	CV3E	744
 Solenoid valve mounted type 	CVS3E	744
Electronic Catalog file list		746

Always read the precautions in the Introduction and page 702 before starting use.

HNB/G

HSR/G

FAB/G FGB/G

FVB

FWB/G

FHB FLB

AR

AG

AD APK/ ADK

For dry air Explosion proof

HVR/ HVL SAR/ SVB

700

NP/NAP/ NVP CHB/G

MXB/G Other G.P.

systems PD/FAD/ P.J

CVSE CPE/

CPD Medica

analysis Custom order

Coolant valve
Air operated 2, 3 port valve